according to Regulation (EC) No 1907/2006

Silatec

Print date: 07.02.2017 Product code: 5010 Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Silatec

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: DMG Chemisch-Pharmazeutische Fabrik GmbH

 Street:
 Elbgaustraße 248

 Place:
 D-22547 Hamburg

 Telephone:
 +49. (0) 40. 84006-0

+49. (0) 40. 84006-0 Telefax: +49. (0) 40. 84006-222

e-mail: info@dmg-dental.com Internet: www.dmg-dental.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Causes serious eye irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Paste

according to Regulation (EC) No 1907/2006

Silatec Print date: 07.02.2017 Product code: 5010 Page 2 of 4

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
68131-39-5	Fatty Alcohol Ethoxylate			< 2.5 %
	Eye Dam. 1, Aquatic Acute 1; H318 H400			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

not applicable

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Store only in original container.

SECTION 8: Exposure controls/personal protection

according to Regulation (EC) No 1907/2006

Silatec

Print date: 07.02.2017 Product code: 5010 Page 3 of 4

8.1. Control parameters

8.2. Exposure controls



Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Skin protection

When using do not eat or drink.

Respiratory protection

No risks worthy of mention.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste

Colour: characteristic
Odour: characteristic

Test method

pH-Value (at 20 °C): not applicable

Changes in the physical state

Initial boiling point and boiling range: > 300 °C
Flash point: > 130 °C
Ignition temperature: > 400 °C
Density: 1,2 - 1,7 g/cm³
Water solubility: insoluble
Vapour density: > 1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat

Decompostion takes place from temperatures above: 100 $^{\circ}\text{C}$

Decomposition under formation of: Formaldehyde.

10.5. Incompatible materials

On contact with water: Formation of: hydrogen.

10.6. Hazardous decomposition products

hydrogen. Formaldehyde.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50: Rat. 5000 mg/kg

according to Regulation (EC) No 1907/2006

Silatec

Print date: 07.02.2017 Product code: 5010 Page 4 of 4

Irritation and corrosivity

Irritant effect on the skin: Not an irritant. Irritant effect on the eve: irritant.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity LC50: > 200 mg/l/96h

12.2. Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Waste disposal number of waste from residues/unused products

180106

WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances

Classified as hazardous waste.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Changes

re-classification of GHS-CLP labeling (H319)

Relevant H and EUH statements (number and full text)

H318 Causes serious eye damage. H319 Causes serious eye irritation. H400 Very toxic to aquatic life.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)