

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaPrint Cast

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

for dental use only

Uses advised against

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG Digital Enterprises SE	
Street:	Elbgaustrasse 248	
Place:	D-22547 Hamburg	
Telephone:	+49 40 84006-0	Telefax: +49 40 84006-222
e-mail:	info@dmg-digital.com	
Internet:	www.dmg-digital.com	
Responsible Department:	Quality Management	

Further Information

The substance does not require registration according to Regulation (EC) No 1907/2006 [REACH].

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 4

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause long lasting harmful effects to aquatic life.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Dimethacrylate Resin

EBPADMA

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Warning

Pictograms:



Hazard statements

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 2 of 7

H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P273 Avoid release to the environment.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P101 If medical advice is needed, have product container or label at hand.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
41637-38-1	Dimethacrylate Resin			50-70 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 4; H315 H319 H317 H335 H413			
41637-38-1	EBPADMA			20-40 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 4; H315 H319 H317 H335 H413			
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			1-2 %
	278-355-8		01-2119972295-29	
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361 H317 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Call a physician immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 3 of 7

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

CO_x, NO_x

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL

8.2. Exposure controls



Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Protective and hygiene measures

When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 4 of 7

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: colourless
 Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: not determined
 Sublimation point: not determined
 Softening point: not determined
 Pour point: not determined
 point of decomposition: not determined estim.
 Flash point: > 93 °C
 Lower explosion limits: not determined
 Upper explosion limits: not determined
 Vapour pressure: not determined
 Density: not determined
 Water solubility: not determined
 (at 20 °C)
 Vapour density: > 1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

Light. heat.
 Decomposition takes place from temperatures above: 200 °C
 Decomposition under formation of: Acrylate.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50: Rat > 2000 mg/kg (calc.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 5 of 7

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 > 5000 mg/kg	Rat	SDS	
	dermal	LD50 > 2000 mg/kg	Rat	SDS	
	inhalation	Data lacking			

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

SECTION 12: Ecological information

12.1. Toxicity

Preparation not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
41637-38-1	EBPADMA					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	(indet)	supplier MSDS	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	(indet)	supplier MSDS	
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	D. magna	supplier MSDS	
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute fish toxicity	LC50 6,53 mg/l	96 h	Oryzias latipes (Ricefish)	SDS	
	Acute algae toxicity	ErC50 > 2,01 mg/l	72 h	Scenedesmus subspicatus	SDS	
	Acute crustacea toxicity	EC50 3,53 mg/l	48 h	Daphnia magna (Big water flea)	SDS	
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	Activated sludge	SDS	

12.2. Persistence and degradability

Preparation not tested.

12.3. Bioaccumulative potential

Preparation not tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

12.4. Mobility in soil

Preparation not tested.

12.5. Results of PBT and vPvB assessment

Preparation not tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 6 of 7

12.6. Other adverse effects

Preparation not tested.

Further information

Do not allow to enter into surface water or drains. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 4; H413	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

LuxaPrint Cast

Revision date: 21.04.2021

Product code: 2420

Page 7 of 7

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)